Permarock Silicone^{Ultra} Façade Coating (Paint)

Overview

Permarock Silicone^{Ultra} Façade Coating is an advanced façade paint. It features an industry-leading nano-quartz matrix technology that provides high resistance to UV degradation, and exceptional performance, even in harsh weather conditions.

Permarock Silicone^{Ultra} Façade Coating dries with a capillary active dry zone that is both water repellent and breathable. Special photocatalytic pigments provide exceptional resistance to pollution-related soiling, while the combination of a Class A binder and Group 1 pigments gives superior UV-stability and colour fastness.

Developed as a breathable, water-repellent coating, Silicone^{Ultra} Façade Coating can be employed as a maintenance coating over external wall insulation and render systems, as well as on brick, concrete and blockwork (masonry) walls.

Permarock Silicone^{Ultra} Façade Coating is particularly suited to providing additional protection against the growth of mould and algae on masonry or render surfaces. It has a flat, matt finish and is available in a wide range of colour-fast shades from the Permarock colour chart.

Quick Check - Silicone^{Ultra} Exterior Coating	
Suitability	PermaRend Exterior Render Systems & Permarock External Wall Insulation Systems
Resistance to Soiling	Excellent: Photocatalytic pigmentation
Colour Fastness	Excellent
Colour Range	1250+
Colour Options	Permarock Colour Chart ´ 5olour matching available
Number of Textures	1
Thickness / Coverage	Circa 150 – 250ml/m² per coat*
Gloss Level	Matt

permarock PRODUCTS LTD

NBS Source PARTNER

Method of Application

Apply with paint brush or roller. The material can be diluted with water or Tiefgrund LF (max 5%) prior to application by brush or roller.

Packaging

Permarock Deep Primer LF comes in 10 ltr buckets. Permarock Silicone^{Ultra} Façade Coating comes in pre-tinted 12.5 ltr buckets.

Coverage Rates

Approx. 150 - 250 ml/m² per coat* on an even substrate - on rough-textured surfaces correspondingly more (exact rate of consumption is best established by a trial coating).

Permarock actively promotes the use of environmentally sound coatings - Silicone^{Ultra} Façade Coating is completely solvent-free, emissions-free and low odour, meeting and surpassing increasingly stringent environmental requirements for protective and decorative coatings.

Permarock Façade Colour Range

The Permarock Colour Chart includes colours with the most light fast and colour stable pigments and are therefore recommended for architectural façades where resistance to fading is a key consideration.

This combination of carefully selected materials confers a number of key benefits over standard colour ranges employed with conventional acrylic and silicone coatings and renders.

Application / Drying Conditions

Please consult our product Technical Data sheets for further information.

* On roughly textured surfaces correspondingly more. The exact amount of material required should be determined by a test area on-site.

Key features

- 500 balanced colour shades over the colour spectrum
- Deep / dark and intensive colour shades with low lightness factors are now available with excellent resistance to fading and chalking
- UV absorbing pigments converts aggressive UV to less harmful longer wavelengths
- Two new inorganic pigments replace UV-unstable orange and blue pigments to provide unprecedented colour fastness in this part of the colour spectrum
- Low lightness factors, light fast / colour fast shades now available

Can't Find The Colour You Require?

- If you can't find your exact colour requirements from our extensive colour palettes, Permarock are able to colour match to RAL, RGB, BS4800 and other widely used commercial colour ranges with many of our decorative finishes. Alternatively, we may also be able to colour match to existing façade shades should you need to closely replicate a colour.
- Note however that colours which do not employ Group 1 pigments cannot be relied upon to have the same level of resistance to fading as those shades featured in the A1 colour range.

All suggestions and application instructions should be used for guidance only

Permarock Products Ltd, Jubilee Drive, Loughborough, Leicestershire, LE11 5TW.
Tel. 01509 262924 | Email. permarock@permarock.com | permarock.com
Connect with Permarock Permarock Products Ltd.

A Sustainable Investments Ltd company

sustainable INVESTMENTS LTD

Version number, 8 June 2025